


# Impresora de Ticket JAW-890

**Xprinter®**

- Cutter life upgrade to 2 million cuts.
- Printhead life upgrade to 150km.
- Easy Maintenance: 5S for firmware update.
- Supports 58/80/82.5mm paper roll width.
- Up to 300mm/s printing speed.
- Steady performance: Apply auto cutter error calibration and printhead overheat protection system.
- Excellent compatibility, rich software on Windows, Linux, Mac, Android, and IOS operating system.





<b>Printing</b>		<b>XP-T890H</b>
Printing method	Direct thermal	
Paper width	58 / 80 / 83±0.5mm	
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm	
Paper roll diameter	Min:13mm Max:83mm	
Column capacity	576 dots/line(adjustable by command)	
Printing speed	300 mm/s	
Interface	USB+Serial+Lan (Optional:Bluetooth/WIFI)	
Line spacing	3.75mm (Adjustable by commands)	
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	
<b>Cutter</b>		
Auto cutter	Partial	
<b>Barcode Character</b>		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 /IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	2048 Kbytes	
NV Flash	256 Kbytes	
<b>Power</b>		
Power adaptor	Input: AC 220V, 50 ~ 60Hz Output: DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
<b>Physical characteristics</b>		
Weight	1.1 Kg	
Dimensions	140*130*133mm(D*W*H)	
<b>Environmental Requirements</b>		
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)	
<b>Reliability</b>		
Cutter life	2 million cuts	
Printer head life	150 KM	
<b>Software</b>		
Emulation	ESC/POS	
Driver	Windows/JPOS/Linux/Android/Mac/OPOS	
Utility	Windows & Linux test Utility	
SDK	iOS/ Android/ Windows	